

Mobile column

EHB907KDC-wireless

article no.: EHB907KDC01-H

Mobile column with a capacity of 7.5 t for light railway vehicles. The load support is carried out by a fixed bracket to lift at the frame. Each column is equipped with a battery drive and radio communication. Per lift set any number of columns can be operated.




specifications


article no.		EHB907KDC01-H
lifting unit	type of columns	all columns identical
load support	load support	bracket, fixed
	capacity per column	7.5 t
	load pad	250 x 250 mm
lifting height	lifting stroke effective	1750 mm
	minimum support height (mm)	150 mm
speed	lifting time	180 sec.
	lowering time (under load)	180 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
power supply	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	20
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
	charging time	8 h
communication		communication via radio, wireless
operation	mode of operation	operation at each column
	activation	all, individual, group
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
travelling device	travelling device	at each column
	travelling device at front	2 front wheels, fixed
	travelling device at rear	1 wheel handle, spring-loaded, self-lowering under load
	ground clearance at front	15 mm
	ground clearance at rear	35 mm
load securing	load securing	hydraulic and mechanical
	lock spacing	15 mm
dimensions	length	1200 mm
	width	1165 mm
	height	2250 mm
weight	weight per column (kgs)	540 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015



accessories




EHB907K-LA01
Support plate




EHB907K-LA02
Hardwood plate




EHB907TDH
hydraulic pallet jack




EHB907FLP
Forklift pockets



EHB907F-SH01
Signal horn



EHB907SPOT02
2 LED spots



EHB907K-VE
Moving device