



Mobile column lifts for tractors

EHB907V11DC / EHB908V11DC + TRT412XXX

article no.: EHB907V11DC01-H / EHB908V11DC01-H + EHB907TRT412XXX

Mobile column EHB907V11DC / EHB908V11DC wireless (capacity 7.5 t / 8.5 t) with basic cross beam of two different widths available, vehicle-dependent load supports for wheel-free lifting of tractors at front and rear. Exemplary combination:

- 2 mobile columns EHB907V11DC: 2 x EHB907V11DC01-H
- 1 basic cross beam for tractor support at front: 1 x EHB907TRT412TR01
- accessories for this basic cross beam depending on the vehicle to be lifted
- 1 basic cross beam for tractor support at rear: 1 x EHB907TRT412TR02
- accessories for this basic cross beam depending on the vehicle to be lifted

**specifications**

article no.		EHB907V11DC01-H / EHB908V11DC01-H + EHB907TRT412XXX
lifting unit	type of columns	all columns identical
	quantity of columns	1
lifting height	lifting stroke effective	1750 mm
speed	lifting time	90 sec.
	lowering time (under load)	90 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 kW
power supply	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	20
	fuse, per column (Amps)	2.5 A
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
charging time	8 h	
communication		communication via radio, wireless
operation	mode of operation	operation at each column
	activation	individual, pair
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
travelling device	travelling device	at each column
	travelling device at front	2 front wheels, fixed
	travelling device at rear	1 wheel handle, spring-loaded, self-lowering under load
	ground clearance at front	15 mm
	ground clearance at rear	35 mm
load securing	load securing	hydraulic and mechanical
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015



accessories



EHB907TRT412TR01

**Basic cross beam 880 mm,
tractor support at front**



EHB907TRT412TR02

**Basic cross beam 640 mm
tractor support at rear**