



Mobile 2-post lift

FHB3000-01-SS-2000

article no.: FHB3000-01

Portable lift, capacity 3000 kg, 400 V power supply, electro-hydraulic drive, symmetric swivel arms, drive-in width 2000 mm, for cars.

Please adhere to the lifting points prescribed by the vehicle manufacturer and check the suitable load supports, the dimensions and the swivelling range of the swivel arms.

**specifications**

| | | |
|--------------------------|---|---|
| article no. | | FHB3000-01 |
| lifting unit | quantity of columns | 2 |
| load support | load support | 4 swivel arms, symmetric |
| | capacity | 3 t |
| | length of swivel arm at front, minimum (mm) | 600 mm |
| | length of swivel arm at front, maximum (mm) | 1070 mm |
| | length of swivel arm at rear, minimum (mm) | 600 mm |
| | length of swivel arm at rear, maximum (mm) | 1070 mm |
| | distance between supports, maximum | 2300 mm |
| | load pad Ø | 120 mm |
| height | lifting height | 1850 mm |
| | minimum support height (mm) | 110 mm |
| | height adjustment of load pad | 35 mm |
| speed | lifting time | 40 sec. |
| | lowering time (under load) | 40 sec. |
| drive | mode of drive | electro-hydraulic |
| | motor | AC voltage |
| | motor power (kW) | 2.2 kW |
| power supply | type of power supply | mains supply |
| | electrical connection | 400V/3Ph+N+PE/50Hz |
| | fuse (Amps) | 16 A |
| | length of power supply cable | 7 m |
| operation | mode of operation | 1 central control unit |
| | control | electric |
| regularisation | synchronisation | master-slave cylinder system |
| travelling device | travelling device | 2 front wheels, 1 detachable wheel handle at rear |
| load securing | load securing | hydraulic and mechanical |
| dimensions | length | 2350 mm |
| | width | 3050 mm |
| | height | 790 mm |
| | drive-in width | 2000 mm |
| weight | | 900 kg |
| protection class | | IP54 |
| surface treatment | type of surface treatment | powder coating |
| | colour | orange RAL2004 / grey RAL7015 |




accessories



FHB3000-LA02

4 extension tubes, 100 mm



FHB3500-Z-UG

U-guidances for rubber pads